

Package: qboxplot (via r-universe)

September 14, 2024

Title Quantile-Based Boxplot

Version 0.2

Date 2017-11-12

Author Tom Pike

Maintainer Tom Pike <tpike@lincoln.ac.uk>

Description Produce quantile-based box-and-whisker plot(s).

Depends stats

Imports methods

License GPL-2

NeedsCompilation no

Date/Publication 2017-11-12 21:41:23 UTC

Repository <https://thomaswpike.r-universe.dev>

RemoteUrl <https://github.com/cran/qboxplot>

RemoteRef HEAD

RemoteSha 63862501f6705488cd9bf8530bd777d07673279a

Contents

qboxplot	2
qboxplot.stats	4
Index	5

qboxplot

*Quantile-Based Boxplots***Description**

Produce quantile-based box-and-whisker plot(s) of the given (grouped) values.

Usage

```
qboxplot(x, range=1.5, probs=c(0.25,0.5,0.75), qtype=7, data=parent.frame(),
         width=NULL, varwidth=FALSE, outline=TRUE, names=NULL, plot=TRUE,
         border=par("fg"), col=NULL, log="", pars=list(boxwex=0.8,
         staplewex=0.5, outwex=0.5), horizontal=FALSE, add=FALSE, at=NULL,
         ...)
```

Arguments

x	a formula, such as $y \sim \text{grp}$, where y is a numeric vector of data values to be split into groups according to the grouping variable grp (usually a factor), or a data frame specifying data from which the boxplots are to be produced.
range	this determines how far the plot whiskers extend out from the box. If range is positive, the whiskers extend to the most extreme data point which is no more than range times the difference between the value of the upper hinge and the value of the lower hinge from the box. A value of zero causes the whiskers to extend to the data extremes.
probs	numeric vector of values in $[0,1]$ specifying the percentiles of the upper hinge, the midpoint (usually the median) and the lower hinge.
qtype	an integer between 1 and 9 indicating which one of the nine quantile algorithms to use (see quantile).
data	a data.frame (or list) from which the variables in formula should be taken.
width	a vector giving the relative widths of the boxes making up the plot.
varwidth	if varwidth is TRUE, the boxes are drawn with widths proportional to the square-roots of the number of observations in the groups.
outline	if outline is FALSE, the outliers are not drawn.
names	group labels which will be printed under each boxplot.
plot	if TRUE then a boxplot is produced. If not, the summaries which the boxplots are based on are returned.
border	an optional vector of colours for the outlines of the boxplots. The values in border are recycled if the length of border is less than the number of plots.
col	if col is non-null it is assumed to contain colors to be used to colour the bodies of the box plots. By default they are in the background colour.
log	character indicating if x or y or both coordinates should be plotted in log scale.
pars	a list of (potentially many) more graphical parameters.

horizontal	logical indicating if the boxplots should be horizontal; default FALSE means vertical boxes.
add	logical, if TRUE add boxplot to current plot.
at	numeric vector giving the locations where the boxplots should be drawn; defaults to 1:n where n is the number of boxes.
...	other arguments (see boxplot).

Value

List with the following components:

stats	a matrix, each column contains the extreme of the lower whisker, the lower hinge, the midpoint, the upper hinge and the extreme of the upper whisker for one group/plot.
n	a vector with the number of observations in each group.
out	the values of any data points which lie beyond the extremes of the whiskers.
group	a vector of the same length as out whose elements indicate to which group the outlier belongs.
names	a vector of names for the groups.

Examples

```
#Example 1
data = data.frame(a=runif(10), b=runif(10), c=runif(10))
qboxplot(data, range=1.3, probs=c(0.2,0.5,0.7), qtype=6)

#Example 2
qboxplot(count~spray, data=InsectSprays, col="lightgray")

#Example 3
rb = qboxplot(decrease~treatment, data=OrchardSprays, log="y", col="bisque")
title("")
rb

#Example 4
mat = cbind(Uni05=(1:100)/21, Norm=rnorm(100), "5T"=rt(100,df=5),
            Gam2=rgamma(100,shape=2))
qboxplot(as.data.frame(mat))

#Example 5
data = c(102,133,136,139,142,144,146,151,160,174)
qboxplot(data.frame(data), range=1.5, probs=c(0.25,0.5,0.75), qtype=1,
          ylim=c(100,220), horizontal=TRUE)
```

qboxplot.stats

Helper Function For qboxplot

Description

Produce quantile-based box-and-whisker plot(s) of the given (grouped) values.

Usage

```
qboxplot.stats(x, probs, qtype, range, output="all")
```

Arguments

x	a numeric vector of data values from which to calculate the requested statistics.
probs	numeric vector of values in [0,1] specifying the percentiles of the upper hinge, the midpoint (usually the median) and the lower hinge.
qtype	an integer between 1 and 9 indicating which one of the nine quantile algorithms to use (see quantile).
output	limit the output to "quantiles", "outliers" or "n" (see below), or, if set to "all" (the default), outputs a list containing all three.
range	this determines how far the plot whiskers extend out from the box. If range is positive, the whiskers extend to the most extreme data point which is no more than range times the difference in the value of the upper hinge and the value of the lower hinge from the box. A value of zero causes the whiskers to extend to the data extremes.

Value

List with the following components:

quantiles	a matrix, each column contains the extreme of the lower whisker, the lower hinge, the median, the upper hinge and the extreme of the upper whisker for one group/plot.
outliers	a vector with the number of observations in each group.
n	the values of any data points which lie beyond the extremes of the whiskers.

Examples

```
x = runif(100)
stats = qboxplot.stats(x, probs=c(0.4,0.5,0.6), qtype=7, range=1.5)
stats
```

Index

- * **qboxplot.stats**
 - qboxplot.stats, 4
- * **qboxplot**
 - qboxplot, 2

boxplot, 3

qboxplot, 2

qboxplot.stats, 4

quantile, 2, 4